

# STEEL FIRE EQUIPMENT LTD

150 Superior Blvd.  
Mississauga, Ontario  
L5T 2L2

## MATERIAL SAFETY DATA SHEET

Prepared to US OSHA, CMA, ANSI and Canadian WHMIS Standards

### PART I What is the material and what do I need to know in an emergency?

#### 1. PRODUCT IDENTIFICATION

**TRADE NAME (AS LABELED):** ABC DRY CHEMICAL  
**SYNONYMS:** Multi-purpose Dry Chemical (56% Model 750)  
**MANUFACTURER'S NAME:** STEEL FIRE EQUIPMENT LTD.  
**ADDRESS:** 150 Superior Blvd  
 Mississauga, Ontario  
 L5T 2L2  
**BUSINESS PHONE:** 905.564.1500  
**DATE OF PREPARATION:** September 9th 2013

#### 2. COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENTS	OSHA PEL	ACGIH TLV	DFG MAK *
Mono-ammonium phosphate	PNOC** Total dust, 15mg/m3 Respirable fraction, 5 mg/m3	PNOC Total dust, 10mg/m3 Respirable fraction, 3 mg/m3	PNOC Total dust, 4mg/m3 Respirable fraction, 1.5 mg/m3
Ammonium sulphate	PNOC Total dust, 15mg/m3 Respirable fraction, 5 mg/m3	PNOC Total dust, 10mg/m3 Respirable fraction, 3 mg/m3	PNOC Total dust, 4mg/m3 Respirable fraction, 1.5 mg/m3
Mica	6 mg/m3	3 mg/m3	NR
Attaclay	NR***	NR	NR
Silicone Oil	NR	NR	NR
Calcium Carbonate	PNOC Total dust, 15mg/m3 Respirable fraction, 5 mg/m3	PNOC Total dust, 10mg/m3 Respirable fraction, 3 mg/m3	_____
Amorphous Silica	143 mg/m3 or <u>80 mg/m3</u> % SiO <sub>2</sub>	10 mg/m3	4 mg/m3
Yellow 14 Pigment	NR	NR	NR

\* German regulatory limits \*\*PNOC = Particulates not otherwise classified (ACGIH) also known as Particulates not otherwise regulated (OSHA) \*\*\* NR = Not Regulated. All values are 8 hour time weighted average concentrations

CHEMICAL NAME/COMPOUND	% W/W	CAS#
Mono-ammonium phosphate and Ammonium sulphate	95	7722-76-1 7783-20-2
Mica	< 3	12001-26-2
Attaclay	< 3	8031-18-3
Silicone Oil	< 1	63148-57-2
Methyl hydrogen polysiloxane		
Calcium Carbonate	< 1	471-34-1
Amorphous Silica	< 1	112926-00-8
Precipitated synthetic zeolite		
Yellow 14 Pigment – di-azo dye	< 1	5468-75-7

### 3. HAZARD IDENTIFICATION & EMERGENCY OVERVIEW

**EMERGENCY OVERVIEW:** This mixture of dry chemicals poses little hazard. Mechanical irritation of the eyes is possible during the use and maintenance of the extinguishing units. Chronic inhalation of any particulate may damage the lungs.

**SYMPTOMS OF OVER-EXPOSURE BY ROUTE OF EXPOSURE:** Over-exposure to this product may cause mild skin irritation, moderate eye irritation, and possible gastric distress. The product is not known to cause chronic illness.

**INHALATION:** Inhalation of this product should be avoided, but if it occurs, may cause mild irritation of the nose, throat, and other tissues of the respiratory system.

**CONTACT WITH SKIN OR EYES:** Contact of dust from this product with the eyes may cause moderate irritation, reddening of the affected eye, and discomfort.

**SKIN ABSORPTION:** No component of this product is known to absorb through the skin.

**INGESTION:** Ingestion of this product may cause gastric distress.



**INJECTION:** While injection of this product is unlikely, it may occur as a result of a puncture or cut with a sharp object contaminated with the extinguishing agent. Mild symptoms, similar to those of skin irritation may occur.

**HEALTH EFFECTS OR RISKS FROM EXPOSURE:** An Explanation in Lay Terms. This product poses low, acute health risks.

**ACUTE:** This extinguishing material presents only a slight risk of causing acute health effects. If such

effects occur, they will be in the form of mild irritation of the skin, nose, or throat and mild irritation of the eyes. If ingested, this product may cause an upset stomach.

**CHRONIC:** This product is not known to cause chronic illnesses or diseases.

HAZARDOUS MATERIAL INFORMATION SYSTEM			
HEALTH		(BLUE)	1
FLAMMABILITY		(RED)	0
REACTIVITY		(YELLOW)	0
PROTECTIVE EQUIPMENT			
EYES	RESPIRATION	HANDS	BODY
	See Section 8		See Section 8
For routine industrial applications			

**PART II What should I do if a hazardous situation occurs?**

**4. FIRST AID MEASURES**

**SKIN EXPOSURE:** If spilled on skin, immediately begin decontamination with running water. Remove exposed or contaminated clothing, taking care not to contaminate eyes. If reddening or irritation occurs, victim and rescuers must seek immediate medical attention.

**EYE EXPOSURE:** If chemical is splashed in eyes, open victim's eyes while under gentle running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 15 minutes.

**INHALATION:** If chemical is inhaled, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. If reddening or irritation occurs, victim and rescuers must seek immediate medical attention.

**INGESTION:** If chemical is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTRE FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow.

If exposure causes obvious distress, victim(s) and rescuers must be taken for medical attention. Take copy of label and MSDS to physician or health professional with victim.

**5. FIRE FIGHTING MEASURES**

**FLASH POINT, C (method):** Not applicable

**AUTOIGNITION TEMPERATURE, C:** Not applicable

**FLAMMABLE LIMITS (in air by volume %) Lower (LEL):** Not applicable

**Upper (LEL):** Not applicable

**FIRE EXTINGUISHING MATERIALS:** None. This product is a fire extinguishing agent.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

When involved in a fire, this material may

decompose and produce irritating fumes and toxic gases including sulfur oxides, carbon dioxide and carbon monoxide.

**Explosion Sensitivity to Mechanical Impact:**

Not sensitive

**Explosion Sensitivity to Static Discharge:**

Not sensitive

**SPECIAL FIRE FIGHTING PROCEDURES:** When


involved incipient fire responders should wear eye protection. Structural fire fighters must wear Self-

Contained Breathing Apparatus and full protective equipment.

**PERSONAL PROTECTION A**  
Safety glasses  
**B** Safety Glasses,  
Gloves  
**C** Safety Glasses,  
Gloves, Apron  
**D** Face Shield, Gloves,  
Apron  
**E** Safety Glasses,  
Gloves, Respirator

**REACTIVITY**  
4 May Detonate  
3 Shock and Heat may  
detonate  
2 Violent Chemical  
Change  
1 Unstable if heated 0  
Stable

**NFPA RANKING**



**HEALTH HAZARD** 4  
Deadly  
3 Extreme Danger 2  
Hazardous  
1 Slightly Hazardous 0  
Normal Material

**FIRE HAZARD**  
**FLASH POINTS**  
4 Below 73 F 3  
Below 100 F  
2 Above 100 F, not  
exceeding 200 F 1  
Above 200F  
0 Will not burn

**6. ACCIDENTAL RELEASE MEASURES**

**SPILL AND LEAK RESPONSE:** Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of spill, clear the affected area, protect people, and respond with trained personnel. If it is determined that exposure guidelines for nuisance particulates – 10mg/m3 (total particulates) or 5mg/m3 (respirable particulates) is exceeded, use

Level C: triple gloves (rubber gloves with nitrile gloves, over latex gloves), chemically resistant suit and boots, hard hat, and purifying respirator with a HEPA filter.  
Sweep up the spilled solid and place all spill residue in a double plastic bag and seal. Dispose of in accordance with Federal, Provincial, and local hazardous waste disposal regulations (see Sections 13).

### **PART III      How can I prevent hazardous situations from occurring?**

#### **7. HANDLING AND STORAGE**

**WORK PRACTICES AND HYGIENE PRACTICES:** Avoid getting chemicals ON YOU or IN YOU. Wash hands after handling chemicals. Do not eat or drink while handling chemicals.

**STORAGE AND HANDLING PRACTICES:** All employees who handle this material should be trained to handle it safely. Avoid breathing dusts generated by this product.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Decontaminate equipment using soapy water before maintenance begins. Collect all rinsates and dispose of according to applicable Federal, Provincial, or local procedures.

#### **8. EXPOSURE CONTROLS - PERSONAL PROTECTION**

**VENTILATION AND ENGINEERED CONTROLS:** Use with adequate ventilation. Use a mechanical fan or vent area to outside.

**RESPIRATORY PROTECTION:** Respiratory protection is not expected to be needed. Maintain airborne contaminant concentrations below guidelines for nuisance particulates: 10 mg/m<sup>3</sup> (total particulates) or 5 mg/m<sup>3</sup> (respirable particulates). If respiratory protection is needed, use only protection authorized in 29CFR 1910.134, or applicable Provincial regulations. Use supplied air respiratory protection if oxygen levels are below 19.5%.

**EYE PROTECTION:** Safety glasses

**HAND PROTECTION:** Wear rubber gloves for routine industrial use. Use triple gloves for spill response, as stated in Section 6 of this MSDS.

**BODY PROTECTION:** Use body protection appropriate for task.

#### **9. PHYSICAL AND CHEMICAL PROPERTIES**

**VAPOR DENSITY:** Not applicable      **EVAPORATION RATE (n-BuAc=1):** Not applicable

**SPECIFIC GRAVITY:** Approximately 0.85      **MELTING POINT RANGE:** Not applicable

**SOLUBILITY IN WATER:** Not soluble. Water repellent coating      **BOILING POINT:** Not applicable

**VAPOR PRESSURE, mm Hg@20 C:** Not applicable      **pH (10% solution):** Approx. 4-5

**APPEARANCE AND COLOUR:** This material is a finely divided, yellowish powder

**HOW TO DETECT THIS SUBSTANCE (warning properties):** This product does not have any specific warning properties.

## 10. STABILITY AND REACTIVITY

**STABILITY:** Stable

**DECOMPOSITION PRODUCTS:** Sulfur oxides, carbon monoxide and carbon dioxide

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** Strong alkalis, magnesium, swimming pool sanitizers (inorganic perchlorates, sodium dichloroisocyanurate dehydrate, trichloroisocyanuric acid, calcium hypochlorite, and other strong oxidizers).

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Incompatible materials

<b>PART IV</b> Is there any other useful information about this material?
---

## 11. TOXICOLOGICAL INFORMATION

**TOXICITY DATA:** The following data is available for components of this product greater than 1% by weight in concentration.

**AMMONIUM SULFATE**

TDL<sub>o</sub> (oral, man) = 150 mg/kg

LD<sub>50</sub> (oral, rat) = 3000 mg / kg

LD<sub>50</sub> (interperitoneal, rat) = 610 mg/kg

**MONOAMMONIUM PHOSPHATE**

No toxicology information listed

**SUSPECTED CANCER AGENT:** This product's ingredients are not found on the following lists: FEDERAL OSHA Z LIST, NTP,CAL/OSHA. A variety of silica forms (i.e. crystalline, fumed) are reported in IARC as a Group 3 Compound (Human Inadequate Evidence: Animal Inadequate Evidence).

**IRRITANCY OF PRODUCT:** This product may cause mild skin and respiratory irritation and moderate eye irritancy.

**SENSITIZATION TO THE PRODUCT:** This product is not known to cause sensitization.

**REPRODUCTIVE TOXICITY INFORMATION:** Listed below is information concerning the effects of this product and its components on the human system.

**Mutagenicity:** This product is not known to cause mutagenic effects

**Teratogenicity:** This product is not known to cause teratogenic effects

**Reproductive Toxicity:** This product is not known to cause reproductive toxicity effects

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Prolonged contact with this product may cause pre-existing dermatitis to become aggravated. Persons sensitive to pulmonary irritation upon exposure to high concentrations of dust should use appropriate engineering controls or respiratory protection when recharging fire extinguishers.

**RECOMMENDATION TO PHYSICIANS:** Treat patient symptoms. This product should not cause any notable clinical symptoms.

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL STABILITY:** No adverse environmental consequences are expected

**EFFECT OF MATERIAL ON PLANTS OR ANIMALS:** None currently known

**EFFECT OF CHEMICAL ON AQUATIC LIFE:** Not expected to harm aquatic life

---

## 13. DISPOSAL CONSIDERATIONS

**PREPARING WASTES FOR DISPOSAL:** Waste disposal must be in accordance with appropriate Federal, Provincial, and local regulations. This chemical, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. Residue from fires extinguished with this material may be hazardous.

---

## 14. TRANSPORTATION INFORMATION

**THIS MATERIAL IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE US DEPARTMENT OF TRANSPORTATION**

<b><u>PROPER SHIPPING NAME:</u></b>	Not applicable
<b><u>HAZARD CLASS NUMBER AND DESCRIPTION:</u></b>	Not applicable
<b><u>UN IDENTIFICATION NUMBER:</u></b>	Not applicable
<b><u>PACKING GROUP:</u></b>	Not applicable
<b><u>DOT LABEL(S) REQUIRED:</u></b>	Not applicable
<b><u>EMERGENCY RESPONSE GUIDE NUMBER:</u></b>	Not applicable
<b><u>MARINE POLLUTANT:</u></b>	Not applicable

**THIS MATERIAL IS NOT HAZARDOUS AS DEFINED BY TRANSPORT CANADA "TRANSPORTATION OF DANGEROUS GOODS" REGULATIONS.**

---

## 15. REGULATORY INFORMATION

**SARA REPORTING REQUIREMENTS:** No component of this product is subject to the reporting requirements of Section 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

**SARA Threshold Planning Quantity:** Not applicable

**TSCA INVENTORY STATUS:** All components are listed on the TSCA Inventory

**CERCLA REPORTABLE QUANTITY (RO):** Not applicable

**OTHER FEDERAL REGULATIONS:** Not applicable

**STATE REGULATORY INFORMATION:** Chemicals in this product are covered under specific State regulations, as denoted below:

Alaska – Designated Toxic and Hazardous Substances: None  
Massachusetts – Substance List: Mica Dust, Ammonium Sulfate  
Pennsylvania – Hazardous Substance List: None

California – Permissible Exposure Limits for Chemical Contaminants: None  
Minnesota – List of Hazardous Substances: None

Rhode Island - Hazardous Substance List: Mica Dust, Ammonium Sulfate  
Florida- Substance List – Mica Dust, Ammonium Sulfate  
Missouri – Employer Information / Toxic Substance List: None  
Texas – Hazardous Substance List: None

Illinois – Toxic Substance List – None.  
North Dakota – List of Hazardous Chemicals, Reportable Quantities. None  
West Virginia – Hazardous Substance List: None

Kansas – Section 302/313 List: None  
Wisconsin – Toxic and Hazardous Substance: None.

**CALIFORNIA PROPOSITION 65:** No component is listed on the California Proposition 65 lists.

**Labelling:** CAUTION! May cause skin or eye irritation. Avoid contact with skin or eyes. In the event of contact, rinse affected part of your body with water for at least 15 minutes. Seek medical attention if reddening or irritation occurs. Keep container tightly closed. Store in a cool, dry location away from incompatible materials. Clean up spills promptly. This product will not contribute to the intensity of a fire.

**TARGET ORGANS:** Skin, eyes

**WHMIS SYMBOLS:** Not applicable

---

## 16. OTHER INFORMATION

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Steel Fire Equipment Ltd. assumes no responsibility for injury to the vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, Steel Fire Equipment Ltd. assumes no responsibility for injury to the vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore vendee assumes the risk in his use of the material.

## DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

**CAS#** - This is the chemical abstract number which uniquely identifies each constituent. It is used for computer related searching.

### EXPOSURE LIMITS IN AIR:

**ACGIH** – American Conference of Government Industrial Hygienists, a professional association which establishes exposure limits.

**TLV** – Threshold Limit Value – an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effects. The duration must be considered, including the 8 hour Time Weighted Average (TWA), the 15 minute Short Term Exposure Limit, and the instantaneous Ceiling Level. Skin absorption effects must also be considered.

**OSHA** – US Occupational Safety and Health Administration

**PEL** – Permissible Exposure Limit – this exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The **IDLH** Immediately Dangerous to Life and Health Level represents a concentration from which one can escape within 30 minutes without suffering escape preventing or permanent injury. The **DFG – MAK** is the Republic of Germany's Maximum Exposure Level, similar to the US PEL. **NIOSH** is the National Institute of Occupational Safety and Health which is the research arms of the US Occupational Safety and Health Administration (OSHA). NIOSH issues exposure guidelines called Recommended Exposure Levels (RELs). When no exposure guidelines are established an entry of **NE** is made for reference.

**FLAMMABILITY LIMITS IN AIR** – Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **LEL** – the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. **UEL** – the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

### TOXICOLOGICAL INFORMATION

Possible health hazards are derived from human data, animal studies or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are:

**LD50** – Lethal Dose (solids and liquids) which kills 50% of the exposed animals

**LC50** – Lethal Concentration (gasses) which kills 50% of the exposed animals

**Ppm** – concentration expressed in parts of material per million parts of air or water

**Mg/m<sup>3</sup>** – concentration expressed in weight of substance per volume of air

**Mg/kg** – quantity of material, by weight, administered to a test subject, based on their body weight in kg.

Data from several sources are used to evaluate the cancer causing potential of the material. The sources are:

**IARC** – the International Agency for Research on Cancer

**NTP** – the National Toxicology Program

**RTECS** – The Registry of Toxic Effects of Chemical Substances, OSHA and CAL/OSHA

IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc) are also used. Other measures of toxicity include:

**TDLo** – the lowest dose to cause a symptom

**TDo, LDLo, and LDo** – the lowest dose to cause death.

### REGULATORY INFORMATION

This section explains the impact of various laws and regulations on the material.



EPA is the US Environmental Protection Agency  
WHMIS is the Canadian Workplace Hazard Information System

DOT and CTC are the US Department of Transportation and the Canadian Transportation Commission, respectively.

SARA – Superfund Amendments and Reauthorization Act  
TSCA – The Toxic Substance Control Act

California Proposition 65 – California Safe Drinking Water Act  
CERCLA – the Comprehensive Environmental Response, Compensation and Liability Act  
This section also includes information on the precautionary warnings which appear on the materials package label.

<b>FIRE EXTINGUISHER</b> Cautions and Warnings
---

Fire extinguishers are designed and produced for the specific purpose of providing a safe and efficient safety tool to be used only in the fighting of fires. Improper or careless use may cause severe bodily injury and / or property damage.

Contents are under pressure which is necessary to deliver the contained extinguishing agent to the fire source. Please take note of the following safety information:

- Contents under pressure. Do not puncture, incinerate, or discharge into another person's face
- Do not store at high temperatures above 120 degrees Fahrenheit or 49 degrees Celsius
- **Keep away from children**
- Avoid inhaling the extinguishing agent. Avoid inhaling smoke and fumes – all fires release toxic substances that are harmful. **DO NOT** remain in a closed area after use; evacuate the area immediately and ventilate thoroughly before re-entering.
- Although extinguishing agents are non toxic when used properly, contact with them may cause irritation to eyes, nose, throat, and other allergic symptoms.

Refer to specific extinguishing agent material safety data sheet for additional information.

<b>AVOID INHALING SMOKE AND FUMES; ALL FIRES RELEASE TOXIC SUBSTANCES THAT ARE HARMFUL. DO NOT REMAIN IN CLOSED AREA AFTER USE. VENTILATE CLOSED AREAS BEFORE RETURNING.</b>
--