

**TREMSTOP IA+ RUST RED-30 CTG CS**Version 2.  
REVISION DATE: 11/22/2010

Print Date 11/23/2010

**SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION****Product Information**Trade name : TREMSTOP IA+ RUST RED-30 CTG CS  
Product code : 917860 323Supplier : Tremco Canada division  
220 Wicksteed Avenue  
Toronto, ON M4H 1G7Telephone : (416) 421-3300  
Emergency Phone: : (613) 996-6666

Product use : Sealant

**Preparation Information**Prepared by: : Sewnauth Raghunandan  
Date: : 11/22/2010  
Telephone : (416) 421-3300**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Rust Red. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**Inhalation : May cause slight irritation to the respiratory system.  
Eyes : Slightly irritating.  
Ingestion : May cause irritation to the mouth, throat and stomach.  
Skin : Irritant effect may be delayed.**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation. Long term overexposure to propylene glycol caused liver abnormalities, kidney damage in laboratory animals. Repeated excessive ingestion may cause central nervous system effects. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**SECTION 3 : HAZARDOUS INGREDIENTS**

**TREMSTOP IA+ RUST RED-30 CTG CS**

Version 2.

Print Date 11/23/2010

REVISION DATE: 11/22/2010

Chemical Name	CAS-No.	Weight % Range
Zinc borate	1332-07-6	10.0 - 30.0
Fibrous Glass	65997-17-3	5.0 - 10.0
Propylene glycol	57-55-6	1.0 - 5.0
Iron oxide	1309-37-1	1.0 - 5.0
Sulfuric acid	7664-93-9	0.5 - 1.5
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0
Chlorothalonil	1897-45-6	0.1 - 1.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Wash with water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5: FIRE / EXPLOSION HAZARDS**

Flash point	:	Not available.
Method	:	Not available.
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings.
Hazardous combustion products	:	Smoke, fumes.
Protective equipment for firefighters	:	Not applicable. Product is not expected to burn.
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

**SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated warehouse location above freezing.



**TREMSTOP IA+ RUST RED-30 CTG CS**

Version 2.  
REVISION DATE: 11/22/2010

Print Date 11/23/2010

**SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Use safety glasses if eye contact is likely.
- Protective measures : Use professional judgment in the selection, care, and use. Other equipment not normally required.

**Engineering measures** : General ventilation is sufficient. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Zinc borate	1332-07-6			
Fibrous Glass	65997-17-3	Ontario TWAEV: ACGIH TWA: Ontario TWAEV: Ontario TWAEV:	5 mg/m3 5 mg/m3 1 ppm 0.5 ppm	Inhalable Inhalable fraction. Respirable fibers Respirable fibers
Iron oxide	1309-37-1	Ontario TWAEV: ACGIH TWA: Ontario TWAEV: ACGIH TWA:	5 mg/m3 5 mg/m3 5 mg/m3 5 mg/m3	Dust and fume.as Fe Respirable fraction. Respirable. Respirable fraction.
Sulfuric acid	7664-93-9	ACGIH TWA: Ontario TWAEV:	0.2 mg/m3 0.2 mg/m3	Thoracic fraction. Thoracic fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	Ontario TWAEV: ACGIH TWA:	0.10 mg/m3 0.025 mg/m3	Respirable fraction. Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Physical State : Paste
- Form : Non-sag gunnable paste
- Color : Rust Red
- Odor : Acrylate
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Miscible
- Evaporation Rate: : Not available.

**TREMSTOP IA+ RUST RED-30 CTG CS**

Version 2.

Print Date 11/23/2010

REVISION DATE: 11/22/2010

Specific Gravity : 1.38  
 % Volatile Weight : 26 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Oxidizing agents.Strong acids.Strong bases.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Propylene glycol, CAS-No.: 57-55-6  
 Acute oral toxicity (LD-50 oral) 30,000 mg/kg ( Rat ) 18,000 mg/kg ( Rabbit ) 19,000 mg/kg ( Dog ) 23,900 - 31,800 mg/kg ( Mouse ) 18,400 - 196,000 mg/kg ( Guinea pig )

Sulfuric acid, CAS-No.: 7664-93-9  
 Acute inhalation toxicity (LC-50) 0.03 mg/l for 8 h ( Guinea pig ) 0.018 mg/l for 8 h ( Guinea pig ) 347 mg/l for 1 h ( Rat )

Chlorothalonil, CAS-No.: 1897-45-6  
 Acute oral toxicity (LD-50 oral) 10,000 mg/kg ( Rat )  
 Acute dermal toxicity (LD-50 dermal) 10,000 mg/kg ( Albino rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - WASTE DISPOSAL CONSIDERATIONS**

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
 NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**  
 All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.



**TREMSTOP IA+ RUST RED-30 CTG CS**

Version 2.

Print Date 11/23/2010

REVISION DATE: 11/22/2010

**Canadian Regulations:**

WHMIS Classification : D2A, D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**Other Regulations:**

Regulatory VOC (less water and exempt solvent) : 54 g/l

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Sewnauth Raghunandan**

**Legend**

- ACGIH - American Conference of Governmental Hygienists
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System